



INTEGRATED POSITIONING UNITS

ULISSE

POSITIONING UNIT

- Made of aluminium and polycarbonate
- IP66
- Easy installation and replacement on-site thanks to optional set-up data in flash memory and accurate mechanical construction
- Horizontal continuous rotation
- Variable speed: 0,1-100°/s Pan; 0,1-40°/s Tilt
- Autopan, Preset, Patrol
- Up to 250 Presets
- OSM configuration
- RS232 interface for PC set-up and firmware upgrade
- RS485, RS422 control
- Version with incremental encoders for real time positioning feedback
- Reinforced heater for low temperature (UPTHT1)
- Multiprotocol
- Integrated wiper option
- Patented



ULISSE, the new positioning unit for dynamic outdoor surveillance. More than a PTZ, more than a Speed Dome, this advanced Videotec product integrates a high performance P&T head with a camera housing and telemetry receiver.



ULISSE WITH INFRARED

POSITIONING UNIT FOR DAY AND NIGHT SURVEILLANCE

- Made of aluminium and polycarbonate
- IP66
- Two infrared LED illuminators for night surveillance
- Available with/without camera and with/without wiper
- Easy installation and replacement on-site thanks to optional set-up data in flash memory and accurate mechanical construction
- Variable speed: 0,1-40°/s Pan; 0,1-30°/s Tilt
- Electronic limit switches
- Autopan, Preset, Patrol
- Up to 250 Presets
- OSM configuration
- Multiprotocol



NEW



ULISSE CAMERA

POSITIONING UNIT WITH INTEGRATED CAMERA

- Telemetry receiver, high performances P&T, camera housing and Sony block camera all-in-one
- Camera for day and night surveillance
- 36x Zoom Lens - High Telephoto Zoom and Wide Horizontal Field of View Capability
- EXView HAD CCD for high sensitivity in low light environments
- High-Performance Digital Signal Processing (DSP)
- Auto ICR (IR cut-filter removal)
- Dynamic Video Masking for privacy purposes
- Reinforced heater for low temperature (UPTHT2)

